

## IQ8Alarm Plus/SpSo sounder with speech, red, composed version



### Part-No. 807322R.SV98

Approval: VdS

Same as 807322R, but with an individual combination of up to 5 languages, see special order form in the appendix.

Addressable, completely bus supplied and short circuit / open circuit resilient voice sounder in compliance with EN 54-3 with integrated voice messages and signaling tones for acoustic alarm signaling.

With up to 20 different programmable signaling tones including DIN tone in accordance with DIN 33404 Part 3.

Speech alarm with 5 pre-programmed alarm messages in 5 different languages.

The volume can be set to 8 different levels.

Selection or combination of speech messages and signaling tones as well the volume control are carried out via the tools 8000 programming software.

Signaling device with flat base, suitable for wall and ceiling mounting.

Optionally, IP base Part No. 806202 with side cable entry and weatherproof protection can be installed.

#### Features:

- Completely bus supplied alarm device
- Powered loop compatible
- Low power consumption
- Up to 24 alarm devices for each powered loop
- Each alarm device has built-in isolator
- Synchronous trigger

#### Acoustic alarm properties:

- EN 54-3 compliant
- High acoustic pressure
- Volume programmable in 8 steps via tools 8000
- 20 different signaling tones, including DIN tone
- Multilingual speech alarm in 5 different languages
- Alarm signaling, evacuation, and test alarm can each be programmed in different languages
- Speech alarm, 5 pre-programmed alarm texts and other country-typical alarm signals

#### Acoustic

Load factor acoustic	4
Sound level	90 db(A) +/- 2 dB @ 1 m / @ 90° / @ DIN tone, for speech & tone 97 db(A) +/- 2 dB @ 1 m / @ 90° / @ DIN tone, only tone
Specification	EN 54-3: 2001 / A1: 2002 / A2 : 2006 / -17: 2005 EN 54-3 Sounder EN 54-3 Voice Sounder

#### Common technical data:

Operating voltage	14 ... 42 V DC (via powered loop)
Quiescent current @ 19 V DC	55 µA
Quiescent current @ FACP battery	approx. 300 µA @ 42 V
Ambient temperature	-10 °C ... 55 °C
Storage temperature	-25 °C ... 75 °C
Air humidity	< 95 % (non-condensing)
Type of protection	IP 43 *2 IP 56 with IP base 806202 *3
Housing	Polycarbonate plastic
Color	red, similar to RAL 3020
Weight	approx. 300 g (with base)
Dimensions	Ø: 112 mm D: 78 mm Ø: 112 mm D: 93 mm (with IP base)
Declaration of Performance	DoP-21430171215



When using the flat IP base the db output reduces by an average of 3 dB  
\*2 IP 21C acc. EN 54-3 / -23

\*3 Do not use the base for acoustic alarm applications in compliance with EN 54-3

Replacement for Part No. 807332.SV98

When ordering, please note the "Order Information for Alarm Signaling Devices IQ8Quad and IQ8Alarm Plus?" and fill in the order form "Order Form for IQ8 Composed Languages (xy.SV98)" printed in the appendix. Cancellations or returns are not possible.



Programmed with an individual selection of up to 5 national languages.

#### Accessories:

806202 IP base, red